



# Declaration of Performance

Kingspan Thermaroom® TR27

1000.CPR.2013.TR27.008

Unique identification code of the product-type: **Kingspan Thermaroom® TR27**  
 Intended use/es: **Thermal insulation for buildings**  
 Manufacturer: **Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK**  
 System/s of AVCP: **System 4 (Reaction to fire), System 3 (Other Properties)**  
 Harmonised technical specification: **BS EN 13165:2012+A2:2016**  
 Notified body/ies: **FIW München: 0751**

Essential characteristics		Performance																														
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	<table border="0"> <tr><td><math>d_N</math> 25mm</td><td>0.90</td></tr> <tr><td><math>d_N</math> 30mm</td><td>1.10</td></tr> <tr><td><math>d_N</math> 40mm</td><td>1.45</td></tr> <tr><td><math>d_N</math> 50mm</td><td>1.85</td></tr> <tr><td><math>d_N</math> 60mm</td><td>2.20</td></tr> <tr><td><math>d_N</math> 70mm</td><td>2.55</td></tr> <tr><td><math>d_N</math> 80mm</td><td>3.20</td></tr> <tr><td><math>d_N</math> 90mm</td><td>3.60</td></tr> <tr><td><math>d_N</math> 100mm</td><td>4.00</td></tr> <tr><td><math>d_N</math> 110mm</td><td>4.40</td></tr> <tr><td><math>d_N</math> 120mm</td><td>5.00</td></tr> <tr><td><math>d_N</math> 130mm</td><td>5.40</td></tr> <tr><td><math>d_N</math> 140mm</td><td>5.80</td></tr> <tr><td><math>d_N</math> 150mm</td><td>6.25</td></tr> <tr><td><math>d_N</math> 160mm</td><td>6.65</td></tr> </table>	$d_N$ 25mm	0.90	$d_N$ 30mm	1.10	$d_N$ 40mm	1.45	$d_N$ 50mm	1.85	$d_N$ 60mm	2.20	$d_N$ 70mm	2.55	$d_N$ 80mm	3.20	$d_N$ 90mm	3.60	$d_N$ 100mm	4.00	$d_N$ 110mm	4.40	$d_N$ 120mm	5.00	$d_N$ 130mm	5.40	$d_N$ 140mm	5.80	$d_N$ 150mm	6.25	$d_N$ 160mm	6.65
	$d_N$ 25mm	0.90																														
	$d_N$ 30mm	1.10																														
$d_N$ 40mm	1.45																															
$d_N$ 50mm	1.85																															
$d_N$ 60mm	2.20																															
$d_N$ 70mm	2.55																															
$d_N$ 80mm	3.20																															
$d_N$ 90mm	3.60																															
$d_N$ 100mm	4.00																															
$d_N$ 110mm	4.40																															
$d_N$ 120mm	5.00																															
$d_N$ 130mm	5.40																															
$d_N$ 140mm	5.80																															
$d_N$ 150mm	6.25																															
$d_N$ 160mm	6.65																															
Thermal conductivity $\lambda_D$ (W/(m.K))	<table border="0"> <tr><td><math>d_N &lt; 80</math>mm</td><td>0.027</td></tr> <tr><td><math>d_N 80-119</math>mm</td><td>0.025</td></tr> <tr><td><math>d_N \geq 120</math>mm</td><td>0.024</td></tr> </table>	$d_N < 80$ mm	0.027	$d_N 80-119$ mm	0.025	$d_N \geq 120$ mm	0.024																									
$d_N < 80$ mm	0.027																															
$d_N 80-119$ mm	0.025																															
$d_N \geq 120$ mm	0.024																															
Thickness tolerance	T2																															
Reaction to fire	Reaction to fire	F																														
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD																														
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD																														
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	Thermal resistance as table above																														
	Thermal conductivity $\lambda_D$ (W/(m.K))	<table border="0"> <tr><td><math>d_N &lt; 80</math>mm</td><td>0.027</td></tr> <tr><td><math>d_N 80-119</math>mm</td><td>0.025</td></tr> <tr><td><math>d_N \geq 120</math>mm</td><td>0.024</td></tr> </table>	$d_N < 80$ mm	0.027	$d_N 80-119$ mm	0.025	$d_N \geq 120$ mm	0.024																								
	$d_N < 80$ mm	0.027																														
	$d_N 80-119$ mm	0.025																														
	$d_N \geq 120$ mm	0.024																														
Durability characteristics	NPD																															
Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1																															
Deformation under specified compressive load and temperature conditions	DLT(2)5																															



# Declaration of Performance

	Determination of the aged values of thermal resistance and thermal conductivity	$\lambda$ D 0,024, 0,025, 0,027 W/m-K
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing Combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....  
**Siobhan O'Dwyer**  
Managing Director  
Pembridge, England, UK  
Date signed: 19/09/2024  
Issue Number: 008



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk)