

- 1. Unique identification code of the product-type: Novia 1600g Radon DPM Gas Barrier
- 2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification as foreseen by the manufacturer: Flexible sheets for waterproofing – Definitions and characteristics (EN 13967:2012)

3. Name and contact address of the manufacturer:

Novia Ltd Unit 3 Trilogy Eurolink V Industrial Park Sittingbourne, Kent ME10 3NH

- Name of the authorised representative whose mandate covers the tasks specified in Article 12, Paragraph 2: N/A
- 5. System of assessment and verification of constancy of performance of the construction product: System 2+
- 6. Notified body: Eurofins 0809

7. Declared Performance:

Essential Characteristics	Technical Performance	Test Standard
Reaction to fire	E	BS EN 13967:2012
Water tightness 2kpa	Pass	
Resistance to impact	200mm	
Resistance to static loading	20kg	
Resistance to tearing MD / CD	250N / 250N	
Durability against heat ageing	Pass	
Durability against chemicals	Pass	
Water vapour resistance	1262 MNs/g	
Water vapour permeability	0.14 g/m²/d	
Tensile properties MD / CD	>15N/mm² / >15N/mm²	
Tensile elongation MD / CD	>400% / >400%	
Shear of joints	>224N/50mm	



The performances of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Acul ewh

Adrian Chisholm, Managing Director Novia Ltd, Sittingbourne, Kent. UK

.....02.04.2025.... Date